

GL/-SS///7E

BALARDO light control BALARDO / BALMERO / CANOPY cloud

LIGHTING SYSTEM





Dear Sir or Madam,

We are now also offering you brilliant lighting for our transparent glass systems. You can use this for your glass canopy, your glass railings and your French balcony. It allows you to emphasise features at night-time, which your visitors will like. The lighting is controlled by intelligent electronics which you can operate simply using an app on your smartphone. This makes it possible for you to choose the colour and intensity of the light with ease. Discover the

new colour and lighting highlights for your building.


Kind regards,

Managing Director















BALARDO light control















A LED strip SMD5050-60-t 6000k

- Light colour: RGBW multi-colour RGB+
- cold white 6000 k
- Dimensions: 5000 x 12 x 2 mm
- IP rating: IP65 ■ Voltage: 24 VDC ■ Beam angle: 120° ■ Brightness: 627 lm/m
- Power consumption: 14.4 W/m
- Number of LEDs: 60/metre
- Can be split every 165 mm (every 10 LEDs)
- Energy efficiency class: A
- Packaging: 5 m/roll
- The item is CE and RoHS-certified



B PowerBox power supply units

Light length: Up to 5 metres Up to 10 metres Up to 20 metres L502408W L502415W L502424W Item no.: 24 VDC 24 VDC 24 VDC Output voltage: Power: 80 watts 151 watts 240 watts Approved for contact Yes with furniture:

Voltage supply: 90-290 VAC + 130-400 VDC 90-290 VAC + 130-400 VDC 90-290 VAC + 130-400 VDC

47-63 Hz ■ Frequency range: 47-63 Hz 47-63 Hz IP67 IP67 IP67 ■ IP rating:

Dimensions (LxBxH): 196 x 62 x 39 mm 222 x 68 x 39 mm 244 x 68 x 39 mm

■ Weight: 1.20 kg 0.84 kg 1.00 kg Cable length: 1 metre 1 metre 1 metre



c GLASSLINE box with APP control

Connection:

- With GLASSLINE APP (Android/iOS)
- With Bluetooth (password-protected)

Control:

- Light on/off
- Continuous dimming
- Set light colour
- Save preferred colour
- Dimensions (L x W x H): 123 x 71 x 30 mm

GL/-SSL//7E BALARDO light control

Accessories

for LED lighting



- **D** 1-metre cable
- Five-pin for RGBW
- **E** 5-metre cable
- Five-pin for RGBW



- F Y-cable
- Five-pin for RGBW




- **G** Dual connector
- Five-pin for RGBW

Structural principle/circuit diagrams




No need for soldering!

- 1 x A LED strip
- 1 x B Power Box
- 1x C GLASSLINE Box







- 1 x B Power Box
- 1x C GLASSLINE Box
- 1 x E 5-metre cable



- 3 x A LED strip
- 1 x B Power Box
- 1 x C GLASSLINE Box
- 3 x E 5-metre cable
- 2x F Y-cable



- 4x A LED strip
- 1 x B Power Box
- 1x C GLASSLINE Box
- 6 x E 5-metre cable
- 2 x F Y-cable



GL/-55///7E

GLASSLINE GmbH

Industriestraße 7-8
74740 Adelsheim
Telefon +49 (0) 6291 6259-0
Fax +49 (0) 6291 6259-11
info@glassline.de

www.glassline.de

SYSTEM SOLUTIONS FOR DEMANDING FRAMELESS GLASS ARCHITECTURE AND SECURE FASTENING OF ATTACHMENTS TO ETICS

GLASSLINE is a leading supplier which develops, manufactures and sells high-quality system solutions in the point support system, all-glass railing system and frameless canopy construction sectors, alongside systems with thermal separation for secure fastening of attachment elements to building envelopes.